SD-999 AG BUILDING & EQUIPMENT CLEANER

ALWAYS READ SAFETY DATA SHEET BEFORE USE!

DIRECTIONS:

BUILDING CLEANING: Before use remove gross contamination with high pressure spray. Wash from the bottom up and rinse from the top down.

MANUAL APPLICATION:

BY MOP, SPONGE, OR BRUSH: Dilute 20-25 parts to 1-part SD-999. Rinse with clear, hot potable water to drain.

FOAM APPLICATION: Dilute 20 to 1 part SD-999 in water. An industrial Foamer should be used. Rinse with clear, hot, potable water to drain. **PRESSURE WASHER:** Dilute 25-30 to 1 part SD-999. For further information contact your local ALKOTA distributor.

FARM EQUIPMENT: For oxidized painted farm equipment apply diluted 10 to 1 with a brush.

CAUTION: Use in a well ventilated area. Can be an irritant to skin and cause eye burns. If swallowed can be harmful.

VOC Content= 293grams per liter HMIS: Health=2


Flammability=0
Reactivity=0

__ GALLONS



THIS APPLIES TO UNDILUTED MATERIAL ONLY!

WARNING STATEMENT



FOR INDUSTRIAL USE ONLY

KEEP AWAY FROM CHILDREN

FOR MEDICAL EMERGENCY CONTACT: ROCKY MOUNTAIN

POSION CENTER @ 303-739-1146. FOR EMERGENCY SPILLS CONTACT:

CHEMTREC: 800-424-9300 OUTSIDE U.S. 703-527-3887

USES: Excellent cleaner & degreaser for hog confinement, poultry operations and any other farm buildings and equipment. It removes the waste contamination in buildings and barns and leaves a citrus scent. It removes a variety of soils including but not limited to fats, proteins, grease, oils etc. 999 is a highly concentrated, non-corrosive, detergent containing a unique blend of alkaline builders, surfactants, natural citrus, and softening agents.

It can be applied through a foamer, pressure washer, mop or brush. With a pleasant citrus scent it will clean up farm equipment in the Fall or anytime. Enhances the color in all farm equipment. Removing the faded oxidized paint on the equipment. This is a permanent change and keeps the finish looking brand new. A USDA letter of guarantee is available upon request. 999 contains Alkota's Scale Trol to protect the machines from scale and hard water build up.

SD-99 contains Ethylene Glycol Monobutyl Ether, Sodium Dodecylbenzene Sulfonate, Sodium Metasilicate, natural citrus, Ethoxylated alcohol and water softening agents.

ALKOTA CLEANING SYSTEMS/DETERGENTS 105 Broad Street Alcester, S.D. 57001

Phone: (712) 859-3980



DETERGENTS. CLEAN SCIENCE.

FIRST AID: EYE CONTACT: Allow streaming water to flow over the face while blinking both eyes for optimum irrigation of both eyes for 15-minutes. Seek medical attention. SKIN CONTACT: In case of contact, wash thoroughly with water. Get medical attention if irritation persists. INGESTION: Do NOT induce vomiting. Drink water. Get medical attention immediately.