TECHNICAL DATA SHEET



ALUMA SHINE 2 TS-602

One of the strongest aluminum brighteners on the market that is highly dilutable making it very economical for use. Great for 90%+ of aluminum brightening applications. One application can make oxidized aluminum look brand new. Removes tough smoke, carbon, grease, oils and built-up road film. Does NOT contain Hydrofluoric Acid. Not for use on polished aluminum, glass or anodized aluminum. Industrial use only.

Product Highlights

- Unique blend of acids and biodegradable surfactants.
- A heavy corrosion inhibitor package minimizes the risk of attacking non-oxidized aluminum.
- Works well in hard or soft water.
- Brightens aluminum, stainless steel, copper, brass, and non-ferrous metals.
- Rapidly removes oxide from aluminum and alloys.
- Reduces sanding/polishing/buffing.
- Contains exclusive antiscale system to prevent scale & coil clogging.
- ♦ Ideal for: Aluminum Trailers.

Physical Description

- ♦ 32% Active Ingredients
- ♦ pH 5% Solution = 1
- Specific Gravity = 1.14
- Does not ship UPS
- ♦ VOC = 1 g/L
- ♦ Shelf Life = 2 years
- Freeze / thaw stable
- ♦ Appearance = Milky white liquid

Application Directions:

- ♦ HEAVY= 1-part TS-602 to 5-parts water.
- ♦ MEDIUM= 1-part TS-602 to 10-parts water.
- ◆ LIGHT= 1-part TS-602 to 20-parts water.

Apply with a pump up sprayer or with a down stream injector. Do not run directly through a pressure washer. Rinse surfaces thoroughly after cleaning with clear, cool, soft, potable water. Wet the surface rapidly with solution of TS-602. Let sit for a few minutes. Do NOT allow product to dry on the surface. Go over the entire surface with brush or pressure spray.

Available in

5 Gallon Pail ♦ 55 Gallon Drum ♦ 275 Gallon Tote
Ships Hazardous

HI PRESSURE EQUIPMENT

#125 – 12051 Horseshoe Way, Richmond, B.C V7A 4V4 604-940-1599 www.hipequip.com